



mr.Kontakt GP®

Based Polymer Dispersion, mineral filling, untreated concrete surfaces, gesso plaster and plaster ground based cement for ceilings and walls
Product code: 70.25.002



About product

mr.Kontakt GP® is a ground based polymer dispersion, mineral filling used before application to flat and even surfaces based cement and gesso. Plasters of gesso base peels off from the surface when enter into a chemical reaction with cement surfaces. It is an excellent ground prepared for to cease the contact and get a strong surface.

Usage fields

✓ used as ground before application of gesso and cement based plasters to untreated concrete surfaces in internal and external places.

Technical specifications

Content of the material	Watery polymer dispersion of mineral filling
Colour	Green
Density	1,6 gr/cm ³
Thickness	Max. 0,4 mm
Drying period	2 hours
Period of plastering	24 hours
Mixture density with water	1,3 gr/sm ³

Above mentioned numbers are given for + 23°C and 50% humidity. High temperature shortens the period and low temperature increases the period.

Advantages

- ✓ Used just mixing with water
- ✓ Increases adherence
- ✓ Prevents speedy absorption of water of applied plaster by the surface.
- ✓ Thus Increases working period preventing

dry cracks in a short time.

- ✓ There is no organic solvent

Application instructions

Preparation of the surface;

The surfaces such as concrete and plaster must be completed durability and cleaned. If the surface is very dirty it must be washed with water or cleaned with moist sponge. All remainder parts must be scoured and cleaned, and strong and clean surface must be available.

Preparation

mr.Kontakt GP® is mixed pouring pure water to its container. The mixture is made till it becomes full homogeneous via mixer 400-600 circle/ min.

Mixture comparison

5 l water is added to 15 kg mr. Kontakt GP and mixed till it becomes homogeneous.

Application

mr.Kontakt GP® is used with disposable roll after it becomes homogeneous mixing with water. Application thickness is defined according to the state of the surface. Usage of it must be increased on the surfaces of high sticking ability.

Consumption

Approximately 150-250 g/m² are applied on the surface.

Cleaning of the tools

Tools and equipments used after application must be cleaned with water.

Storage conditions

Store in an unopened original packing, cool and dry place without freezing

Storage term

Best before is one year from manufacture date under correct storage conditions

Safety measures

During the application, uniform, protective glove, glasses and mask suitable for the working and health conditions must be used. For negative effects of raw material, do not touch the contents to the skin and eyes, otherwise you must wash the same region with water and soap well and if you swallow it apply to the doctor immediately. Do not allow the foodstuffs to the areas where the material is applied. Keep out of reach of children. For detailed information please refer to the Safety Information Form.

Responsibility

Mr. Fix is only responsible for the quality of the product and our company is not responsible for the usage out of written offers regarding where and how the product shall be used or dangerous usages. We ask you to demand product manual and contact with responsible persons regarding the necessary support.

Net: 15 kg ±2%

