

Lineflex® Dilatasyon Banti

Lineflex Deformative Tapes

Product code: 31.DLT.

About product

Lineflex deformative tapes - is a propylene and ethylene based synthetic rubber deformative tape using in water isolation of deformative areas of all kind building.

Usage field

✓ Use in water isolation of deformative areas of all kind structure.

Advantages

✓ Not lose elasticity in high temperature changes

- ✓ Not lose draw resistant in high temperature changes
- ✓ Keep elasticity in high temperature changes
- ✓ Not lose elasticity in changeable weather conditions
- ✓ Sunbeam and ozone resistant
- ✓ Ascite and chemical mixture resistant
- ✓ More than 300% elasticity



Thickness	Product code
Lineflex EPDM DLT tape 15 cm	31.DLT.15
Lineflex EPDM DLT tape 20 cm	31.DLT.20
Lineflex EPDM DLT tape 25 cm	31.DLT.25
Lineflex EPDM DLT tape 30 cm	31.DLT.30
Lineflex EPDM DLT tape 45 cm	31.DLT.45

Technical Specifications

Content of the material	Propylene and ethylene synthetic rubber
Static load resistant	20 kg
Draw resistance	
Equipped board	7,01 MPa
Unequipped board	8,62 MPa
Elongate	+5°C +25°C
Tear resistant	
Equipped board	82,72 N/mm
Unequipped board	426,11 N/mm
Fire resistant	Euroclass
Additional place slipping resistant	5,74 N/mm
Additional place peel resistant	3,70 N/mm





Lineflex EMT adhesive

Lineflex EMT adhesive: This is adhesive with solvent ensuring the adhesion of EPDM membrane to each other strongly. The additional



places of membrane shall fall in succession 10 cm while application. The application area must be clean and without humid. It applied



with clean brush to both surfaces. Average application amount is 150 gr/m².



Lineflex KNT adhesive

Lineflex KNT adhesive : it is used in the adhesion of EPDM membrane to EPDM external different surfaces such as wood, metal. The application area must be clean and without humid. Average application amount is 500 gr/m² according to the place of application and is adhered pressing strongly after rubbing to both sides and waiting for 10-15 minutes.

Lineflex® Mastik

Lineflex Mastik : It is applied to fill completion details among EPDM membrane and pressing plate. This is a silicone filling EPDM based prevention of water leakage. It is high level product with elastic feature, perfect adhesion to the surfaces such as concrete, wood, metal and plastic. Packed in 310 ml cartridge and 600 ml frankfurter. The application area must be clean and without humid. Average application amount is 50 ml/ mt. hardening period is 1-24 hours depending on weather conditions, place of application and technique.

Safety measures

During the application, uniform, protective glove, glasses and mask suitable for the working and health conditions must be used. For negative effects of raw material, do not touch the contents to the skin and eyes, otherwise you must wash the same region with water and soap well and if you swallow it consult to the doctor



immediately. Keep out of reach of children. For detailed information please refer to the Safety Information Form.

Responsibility

Mr. Fix is only responsible for the quality of the product and our company is not responsible for the usage out of written offers regarding where and how the product shall be used or dangerous usages. We ask you to demand product manual and contact with responsible persons regarding the necessary support.

