

TECHNICAL DATASHEET

PRATIX® S

About Product

PRATIX® S is a cement-based plastering material with polymer additives for aerated concrete and concrete surfaces

Product code: 204.30003

Advantages

- Easy to prepare and apply
- Designed specially for aerated concrete surfaces
- Long open time
- High adhesion strength
- Resistant to cracking and strokes
- Forms a durable layer on the surface of aerated concrete
- Paint and wallpaper can be applied directly to the product
- Can be used indoors and outdoors
- Resistant to freeze and thaw cycles

Application Areas

- In indoor and outdoor applications
- In plastering walls made of aerated concrete
- On cement-based surfaces to obtain a smooth surface before painting

Technical Specifications

Composition of material	Mineral aggregates, synthetic additives, polymer, and special cement
Color	White
Adhesion strength	$\geq 0.50 \text{ N/mm}^2$
Open time	20 min
Application time	2 hours
Application temperature	+5°C + 25°C
Service temperature	-20°C + 80°C
Largest aggregate grain size	Max. 1 mm

TECHNICAL DATASHEET

PRATIX® S

Mix density	~1.67 kg/L
-------------	------------

Consumption	7kg /m ² (5 mm)
-------------	----------------------------

The above figures are valid for +20°C and relative humidity of 50%. High temperatures accelerate the process while low temperatures extend it.

Application Guidelines

Surface Preparation

Ensure the treated surface to be healthy, dry, clean, dust-free, and load-bearing. The surface should be free of oil, paint, rust, and wax residues preventing adhesion. Do not use in weather conditions with a risk of freezing within 24 hours. Do not apply in direct sunlight, strong wind, or rainy weather.

Preparing the Mix

Pour water into a clean container, slowly add the **PRATIX® S** plastering material, and mix using a mixer at 400-600 rpm for 3-5 minutes until disaggregation. After about 3-5 minutes, mix again for 1 minute. Then, the product is ready for use. Do not use the hardened mix by adding water.

Mixing Ratio

per 1 kg powder	~ 0,23 L water
-----------------	----------------

per 25 kg powder	~ 5.75 L water
------------------	----------------

Consumption

5 kg/m² of powder per 5 mm thick layer

Cleaning Tools

After application clean the used tools and accessories immediately with water. If hardened, the product can only be removed from the surface mechanically.

Storage Conditions

Store unpacked in the original packaging (container) in a dry and cool place.

TECHNICAL DATASHEET

PRATIX® S

Shelf Life

Under proper storage conditions 12 months from the date of manufacture.

Safety Measures

During the application wear work clothes and use protective gloves, glasses, and a mask according to the working conditions and occupational safety requirements. Due to the irritant effect of the uncured material, avoid contact with skin and eyes; in case of contact, immediately wash the contact area with plenty of water and soap; in case of ingestion, seek medical advice immediately. Food products should not be allowed in the material application areas. Store out of reach of children. For more details, please see the Safety Datasheet.

Liability

Our company shall only be liable for the product quality. Our company shall not be liable for any use of the product in breach of written guidelines and/or improper use. For more details, please request a product manual or contact our company's responsible officials.

Net weight: 25 kg



KARTAS LTD LLC

7, Binagadi settlement, Binagadi district, Baku

www.mrfix.az

Phone: +994 12 347 00 10, +994 12 347 10 10